


# TRAIL: ZONE LOWBAY



Teknoware Trail is an elegant emergency light that is easy to install on a lighting track. Thanks to its unique design, it is suitable for direct mounting on common lighting track systems. The luminaire can also be mounted directly on the ceiling. Trail has a modern and streamlined appearance so it blends in with the surroundings and architecture. Trail’s wide product family and range of optics offer many options to suit a variety of applications and systems.

Trail Zone Lowbay is particularly suitable for low spaces. The luminaire provides a broad, uniform light pattern that illuminates open areas efficiently.

- for open areas
- self-contained or centrally supplied depending on model
- installation: surface mounting on a lighting track (compatible with Global Trac and lighting trunking systems) or ceiling mounted
- material: metal casing
- colour: white (RAL 9003), other RAL-colours on request
- SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND SELF-TESTING

Product Code	Nominal Supply Voltage	Feature	Backup (h)	Form
TWSC292WM	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	
TWSC292WMC	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	

## SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND WIRELESS CENTRAL MONITORING

We reserve the rights to make modifications without notice.  
Copyright © 2024 Teknoware. All rights reserved.  
Date: May 18, 2024 | Source:  
[www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/trail-zone-lowbay](http://www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/trail-zone-lowbay)



Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWSC292WA	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1
TWSC292WAC	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1

## SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND SELF-TESTING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWTC252WM	220-240 V, 50/60 Hz AC	Lumi Test	1
TWTC253WM	220-240 V, 50/60 Hz AC	Lumi Test	3

## SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWTC252WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	1
TWTC253WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	3

## ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature
TWTC251WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control

## NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWTC271W	24-230 V, 50/60 Hz AC, DC		

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: May 18, 2024 | Source:

[www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/trail-zone-lowbay](http://www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/trail-zone-lowbay)



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland

Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)