


LINESPOT II: LOWBAY, SURFACE-MOUNTED EMERGENCY LIGHTS



The Linespot II Lowbay is a surface-mounted emergency light that is particularly suitable for low spaces. The luminaire's optics are designed to provide a long and

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: May 19, 2024 | Source:

www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/linespot-ii-lowbay-surface-mounted-emergency-lights



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com

narrow light pattern that illuminates corridors and escape routes efficiently

Thanks to the IP44 enclosure class Linespot II is also suitable for damp locations. Linespot II is easy and fast to install thanks to a separate mounting base, which is also connected to the power supply.

SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND SELF-TESTING

Product Code	Nominal Supply Voltage	Feature	Backup (h)	Form
TWS9992WMT	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	
TWS9992WM	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	
Y9992WM	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	

SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWS9992WAT	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1
TWS9992WA	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1
Y9992WA	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND SELF-TESTING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWT9952WMT	220-240 V, 50/60 Hz AC	Lumi Test	1
TWT9953WMT	220-240 V, 50/60 Hz AC	Lumi Test	3
TWT9953WM	220-240 V, 50/60 Hz AC	Lumi Test	3
Y9953WM	220-240 V, 50/60 Hz AC	Lumi Test	3
TWT9952WM	220-240 V, 50/60 Hz AC	Lumi Test	1
Y9952WM	220-240 V, 50/60 Hz AC	Lumi Test	1

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWT9952WAT	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	1
TWT9953WAT	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	3
TWT9953WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	3
Y9953WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	3

We reserve the rights to make modifications without notice.
Copyright © 2024 Teknoware. All rights reserved.
Date: May 19, 2024 | Source:
www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/linespot-ii-lowbay-surface-mounted-emergency-lights

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWT9952WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	1
Y9952WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	1

ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature
TWT9951WKT	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control
Y9951WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control
TWT9951WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control

NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWT9971WT	24-230 V, 50/60 Hz AC, DC		
TWT9971W	24-230 V, 50/60 Hz AC, DC		
Y9971W	24-230 V, 50/60 Hz AC, DC		

ADDRESSABLE 24 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWT9941WKT	24 V, 50/60 Hz AC, DC	Tapsa Control	
TWT9941WK	24 V, 50/60 Hz AC, DC	Tapsa Control	
Y9941WK	24 V, 50/60 Hz AC, DC	Tapsa Control	

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: May 19, 2024 | Source:

www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/linespot-ii-lowbay-surface-mounted-emergency-lights

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com

