#### ESC 90 EMERGENCY EXIT LIGHT TWS9092WMT































# Self-contained emergency exit light with 1 h super capacitor and self-testing

The ESC 90 is an emergency exit light that combines cutting-edge technology with modern lighting design. Thanks to high quality electronics, optics and mechanical design, the luminaire has uniformly illuminated pictograms and low power consumption.

Changing the pictograms is easy and the plastic sheet slides easily into place. The ESC 90 exit light is easy to install on the ceiling or on a wall. It can be used 1 or 2 sided, with either recess or surface mounting. The ESC 90 is particularly easy and fast to install thanks to the separate mounting piece, which the power supply is also connected to.



Product Code	TWS9092WMT
Feature	Escap, Lumi Test
Mounting (standard)	ceiling, wall
Mounting (optional)	recess, flag, pendel
Customs Code	94056080
GTIN Code	06438045028477
ETIM Product Class	EC001957
Length	268 mm
Width	40 mm
Height	202 mm
Weight	0,6 kg
Backup	1h
Max Input Power VA	4 VA
Nominal Supply Voltage	220-240 V, 50/60 Hz AC
Protection Class	
IP Class	IP44
Temperature Range Min - Max	-25+35 °C
Glow Wire Test of Plastic Materials	850 °C
Viewing Distance	25 m
Light Source	LED
Body Material	plastic
Aperture for Recess Mounting	45 x 275 mm
Colour	RAL9005
Electrical Installation	2/3 x 2,5 mm <sup>2</sup>

## ONE OR MORE OF THESE IS ALSO REQUIRED:

### PICTOGRAMS FOR EMERGENCY EXIT





#### LIGHTS

Product Code	Pictogram	Viewing Distance (m)	Compatible Product Groups
PB401	S→ < 2 + 2 + 2	25	ESC 90 Emergency Exit Lights
PB9004	€ 2	25	ESC 90 Emergency Exit Lights
PB9005	<b>₹</b>	25	ESC 90 Emergency Exit Lights
PB9006	<b>₹</b>	25	ESC 90 Emergency Exit Lights

## **OPTIONAL ACCESSORIES:**

# SHOCK PROTECTING COVERS FOR **EMERGENCY LIGHTS**



Product Code	Product Name	Compatible Product Groups
TW77508B	Shock protecting cover TW77508B	ESC 0,5 Emergency Exit Lights, ESC 4 Emergency Exit Lights, ESC 90 Emergency Exit Lights, Safe 82 Emergency Lights





