


# SLIMSPOT II: LINE MIDBAY



Slimspot II is a recessed emergency light that is effective and seamless. It has an elegant and minimalist appearance, so it blends in with the surroundings and architecture. The broad Slimspot II product family and range of optics offers many options to suit a variety of applications and systems. Slimspot II is designed for indoor lighting, and it has durable metal framing. The standard colour of the luminaire is white. On request, it is also possible to order Slimspot II in black and grey to match the surrounding environment.

The Slimspot II Line Midbay provides a long and narrow pattern that illuminates escape routes efficiently.

- for escape routes
- self-contained or centrally supplied depending on model
- IP rating: IP20
- installation: recess-mounted
- material: metal framing
- standard colour: white (RAL 9003)
- optional colours: black (RAL 9005) and grey (RAL 9006)
- SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND SELF-TESTING

Product Code	Nominal Supply Voltage	Feature	Backup (h)	Form
TWSA492WM	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	■
TWSA492WM4	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	■
TWS1192WM4	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	●
TWS1192WM	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	●

We reserve the rights to make modifications without notice.  
Copyright © 2024 Teknoware. All rights reserved.  
Date: May 08, 2024 | Source:  
[www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/slimspot-ii-line-midbay](http://www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/slimspot-ii-line-midbay)



## SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWSA492WA	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1
TWSA492WA4	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1
TWS1192WA4	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1
TWS1192WA	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1

## SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND SELF-TESTING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWTA452WM	220-240 V, 50/60 Hz AC	Lumi Test	1
TWTA453WM	220-240 V, 50/60 Hz AC	Lumi Test	3
TWT1152WM	220-240 V, 50/60 Hz AC	Lumi Test	1
TWT1153WM	220-240 V, 50/60 Hz AC	Lumi Test	3

## SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWTA452WA	220-240 V, 50/60 Hz AC	Aalto Control	1
TWTA453WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	3
TWT1152WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	1
TWT1153WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	3

## ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature
TWTA451WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control
TWT1151WKP	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control
TWT1151WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control

## NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWT1171W	24-230 V, 50/60 Hz AC, DC		●

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: May 08, 2024 | Source:

[www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/slimspot-ii-line-midbay](http://www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/slimspot-ii-line-midbay)



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland

Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)

Product Code	Nominal Supply Voltage	Feature	Form
TWTA471W	24-230 V, 50/60 Hz AC, DC		■

ADDRESSABLE 24 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWT1141WK	24 V, 50/60 Hz AC, DC	Tapsa Control	●
TWTA441WK	24 V, 50/60 Hz AC, DC	Tapsa Control	■