


ZONESPOT II: ANGLE



Teknoware Zonespot II Angle is a surface-mounted emergency light that illuminates safety equipment, such as fire alarm call points, first aid stations, firefighting equipment and panels, vertically with 5 lux according to EN 1838. Zonespot II Angle has been designed for indoor lighting, and the standard colour is white (RAL 9003). Installation is quick and easy, with a separate mounting base that also handles the power supply connection.

- A surface-mounted emergency light
- Illumination for first aid and firefighting equipment
- Illuminance of 5 lux, in compliance with the EN 1838 standard
- 45° tilt angle for the lighting pattern
- Housing with protection class: IP40
- Standard colour: White (RAL 9003)
- SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND SELF-TESTING

Product Code	Nominal Supply Voltage	Feature	Backup (h)	Form
TWSD292WM	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	

We reserve the rights to make modifications without notice.
Copyright © 2024 Teknoware. All rights reserved.
Date: May 08, 2024 | Source:
www.teknoware.com/en/our-solutions/emergency-lighting-buildings/emergency-lights/emergency-light-product-families/zonespot-ii-angle

SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWSD292WA	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND SELF-TESTING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWTD252WM	220-240 V, 50/60 Hz AC	Lumi Test	1
TWTD253WM	220-240 V, 50/60 Hz AC	Lumi Test	3

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWTD252WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	1
TWTD253WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	3

ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature
TWTD251WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control

NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWTD271W	24-230 V, 50/60 Hz AC, DC	Tapsa Control	

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: May 08, 2024 | Source:

www.teknoware.com/en/our-solutions/emergency-lighting-buildings/emergency-lights/emergency-light-product-families/zonespot-ii-angle

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com

