


# SOLID: ZONE LOWBAY EMERGENCY LIGHTS



Solid Zone Lowbay has been developed for the emergency lighting of open areas.

High enclosure class (IP65) ensures that the luminaire is completely dustproof and waterproof. Solid Zone Lowbay is suitable for example for industrial premises, parking halls, and outdoor use. The Solid luminaire uses long-lasting LEDs as its light source.

Special attention has been paid to the design, for easy installation.

## SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND SELF-TESTING

Product Code	Nominal Supply Voltage	Feature	Backup (h)	Form
TWS3292WM	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	
Y3292WM	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	

## SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWS3292WA	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1
Y3292WA	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1

## SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND SELF-TESTING

We reserve the rights to make modifications without notice.  
Copyright © 2024 Teknoware. All rights reserved.  
Date: April 26, 2024 | Source:  
[www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/solid-zone-lowbay-emergency-lights](http://www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/solid-zone-lowbay-emergency-lights)

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland  
Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)



Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWT3252WM	220-240 V, 50/60 Hz AC	Lumi Test	1
Y3252WM	220-240 V, 50/60 Hz AC	Lumi Test	1
TWT3253WM	220-240 V, 50/60 Hz AC	Lumi Test	3
Y3253WM	220-240 V, 50/60 Hz AC	Lumi Test	3

## SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWT3252WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	1
Y3252WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	1
TWT3253WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	3
Y3253WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	3

## ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature
TWT3251WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control
Y3251WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control

## NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWT3271W	24-230 V, 50/60 Hz AC, DC		
Y3271W	24-230 V, 50/60 Hz AC, DC		

## ADDRESSABLE 24 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWT3241WK	24 V, 50/60 Hz AC, DC	Tapsa Control	

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: April 26, 2024 | Source:

[www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/solid-zone-lowbay-emergency-lights](http://www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/solid-zone-lowbay-emergency-lights)



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland  
Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)