

PICTOGRAM PBV80202E



2-sided, light plate pictogram, arrow down, for Esc 80 (TWT80/TWS80) emergency exit lights.
20 m viewing distance.

Product Code	PBV80202E
Customs Code	94056080
GTIN Code	6438045014142
ETIM Product Class	EC000479
Length	268 mm
Width	10 mm
Height	100 mm
Weight	0,4 kg
Viewing Distance	20 m

ONE OR MORE OF THESE IS ALSO REQUIRED:

SELF-CONTAINED ESCAP EMERGENCY EXIT
LIGHTS WITH SUPER CAPACITOR AND
SELF-TESTING



Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWS8092WM	220-240 V, 50/60 Hz AC		2-sided, 20/26/30 m	1

SELF-CONTAINED ESCAP EMERGENCY EXIT
LIGHTS WITH SUPER CAPACITOR AND
WIRELESS CENTRAL MONITORING



Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWS8092WA	220-240 V, 50/60 Hz AC		2-sided, 20/26/30 m	1

SELF-CONTAINED EMERGENCY EXIT
LIGHTS WITH BATTERY AND SELF-TESTING



Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWT8053WM	220-240 V, 50/60 Hz AC		2-sided, 20/26/30 m	3

We reserve the rights to make modifications without notice.
Copyright © 2024 Teknoware. All rights reserved.
Date: May 10, 2024 | Source: www.teknoware.com/en/pictogram-pbv80202e

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com



SELF-CONTAINED EMERGENCY EXIT LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING



Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWT8053WA	220-240 V, 50/60 Hz AC		2-sided, 20/26/30 m	3

ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY EXIT LIGHTS



Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info
TWT8051WK	220-240 V, 50/60 Hz AC, DC		2-sided, 20/26/30 m

NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY EXIT LIGHTS



Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info
TWT8051W	220-240 V, 50/60 Hz AC, DC		2-sided, 20/26/30 m

NON-ADDRESSABLE 24 V CENTRALLY SUPPLIED EMERGENCY EXIT LIGHTS



Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info
TWT8041W	24 V, 50/60 Hz AC, DC		2-sided, 20/26/30 m

