

PICTOGRAM PBV80302E3



1-sided, light plate pictogram, arrow down, for Esc 80 (TWT80/TWS80) emergency exit lights. 30 m viewing distance.

Product Code	PBV80302E3
Customs Code	94056080
GTIN Code	6438045020761
ETIM Product Class	EC000479
Length	268 mm
Width	10 mm
Height	173 mm
Weight	0,8 kg
Glow Wire Test of Plastic Materials	650 °C
Viewing Distance	30 m

ONE OR MORE OF THESE IS ALSO REQUIRED:

SELF-CONTAINED ESCAP EMERGENCY EXIT
LIGHTS WITH SUPER CAPACITOR AND
SELF-TESTING



Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWS8092WM	220-240 V, 50/60 Hz AC		2-sided, 20/26/30 m	1

SELF-CONTAINED ESCAP EMERGENCY EXIT
LIGHTS WITH SUPER CAPACITOR AND
WIRELESS CENTRAL MONITORING



Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWS8092WA	220-240 V, 50/60 Hz AC		2-sided, 20/26/30 m	1

SELF-CONTAINED EMERGENCY EXIT
LIGHTS WITH BATTERY AND SELF-TESTING



We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: May 12, 2024 | Source: www.teknoware.com/en/pictogram-pbv80302e3

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com



Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWT8053WM	220-240 V, 50/60 Hz AC		2-sided, 20/26/30 m	3

SELF-CONTAINED EMERGENCY EXIT LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING



Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWT8053WA	220-240 V, 50/60 Hz AC		2-sided, 20/26/30 m	3

ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY EXIT LIGHTS



Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info
TWT8051WK	220-240 V, 50/60 Hz AC, DC		2-sided, 20/26/30 m

NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY EXIT LIGHTS



Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info
TWT8051W	220-240 V, 50/60 Hz AC, DC		2-sided, 20/26/30 m

NON-ADDRESSABLE 24 V CENTRALLY SUPPLIED EMERGENCY EXIT LIGHTS



Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info
TWT8041W	24 V, 50/60 Hz AC, DC		2-sided, 20/26/30 m

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: May 12, 2024 | Source: www.teknoware.com/en/pictogram-pbv80302e3

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com



