AALTO CONTROL WIRELESS MONITORING UNIT (WMU) TST5108









Wall mounted Aalto Control Wireless Monitoring Unit With Aalto Control Wireless Monitoring Unit (WMU) you can monitor and control self-

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: April 25, 2024 | Source:

www.teknoware.com/en/emergency-lighting/aalto-control-wireless-monitoring-unit-wmu-tst 5108



contained Aalto Control luminaires, both ESCAP luminaires and luminaires with batteries. The monitoring unit, with an easy-to-use 7" touch screen and a clear user interface, is mounted permanently on the wall. Aalto Control WMU has an indoor range of 40 meters to the nearest luminaire, the same as from luminaire to other luminaires.

AALTO CONTROL WMU FEATURES

into other systems

Works independently, without a separate PC or Coordinator
Possibility to add one external Coordinator via Ethernet
Functions on AC power, does not interfere with the electrical supply to the luminaires
History data files of the luminaires can be stored on a USB stick
Prohibition times can be defined for luminaire and duration time tests
Definable and selectable levels of user access
Saving of luminaire and location information and the test history in a database
The relay output with indication of fault condition enables the transmission of fault information

Product Code	TST5108
Mounting (standard)	wall
GTIN Code	6438045019581
ETIM Product Class	EC000783
Nominal Supply Voltage	220-240 V, 50 Hz AC
IP Class	IP20











