
## SLIMSPOT II LINE LOWBAY EMERGENCY LIGHT TWS6192WA





## Self-contained Escap Emergency light with 1 h super capacitor and wireless central monitoring

Slimspot II is a recessed emergency light that is effective and seamless. It has an elegant and minimalist appearance, so it blends in with the surroundings and architecture. The broad Slimspot II product family and range of optics offers many options to suit a variety of applications and systems. Slimspot II is designed for indoor lighting, and it has durable metal framing. The standard colour of the luminaire is white. On request, it is also possible to order Slimspot II in black and grey to match the surrounding environment.

The Slimspot II Line Lowbay provides a long and narrow pattern that illuminates escape routes

We reserve the rights to make modifications without notice. Copyright © 2024 Teknoware. All rights reserved. Date: May 03, 2024 | Source: www.teknoware.com/en/emergency-lighting-1/slimspot-ii-line-lowbay-emergency-light-tws6 192wa



efficiently.

We reserve the rights to make modifications without notice. Copyright © 2024 Teknoware. All rights reserved. Date: May 03, 2024 | Source: www.teknoware.com/en/emergency-lighting-1/slimspot-ii-line-lowbay-emergency-light-tws6 192wa



Product Code	TWS6192WA		
Feature	Aalto Control, Escap, Lumi Test		
Mounting (standard)	recess		
Customs Code	94056080		
GTIN Code	6438045025544		
ETIM Product Class	EC001957		
Length	90 mm		
Width	90 mm		
Height	46 mm		
Weight	0,8 kg		
Backup	1h		
Max Input Power VA	3 VA		
Nominal Supply Voltage	220-240 V, 50/60 Hz AC		
Protection Class	1		
IP Class	IP20		
Temperature Range Min - Max	-25+35 °C		
Glow Wire Test of Plastic Materials	850 °C		
Light Source	LED		
Body Material	plastic		
Aperture for Recess Mounting	ø75 mm		
Colour	RAL9003		
Electrical Installation	3 x 2,5 mm²		
Luminous Flux	75 lm		


## Emergency lighting for escape routes (ceiling mounting)

Table of 1 lux for escape routes in the middle line according to the norm EN 1838. Level of measurement 0,02 m, measurement result with battery operation.

We reserve the rights to make modifications without notice. Copyright © 2024 Teknoware. All rights reserved. Date: May 03, 2024 | Source:

www.teknoware.com/en/emergency-lighting-1/slimspot-ii-line-lowbay-emergency-light-tws6 192wa






R1 distance from wall (X axis) R2 installation distance between lights (X axis) R4 distance from wall (Y axis) TWS6192WA

Mounting height (m)	Below the light lux	R1 (m)	R2 (m)	R4 (m)
		1 lux	1 lux	1 lux
2,5	2,5	5	16	1
3	1,5	4,5	16,5	1

We reserve the rights to make modifications without notice. Copyright © 2024 Teknoware. All rights reserved. Date: May 03, 2024 | Source: www.teknoware.com/en/emergency-lighting-1/slimspot-ii-line-lowbay-emergency-light-tws6

192wa





We reserve the rights to make modifications without notice. Copyright © 2024 Teknoware. All rights reserved. Date: May 03, 2024 | Source: www.teknoware.com/en/emergency-lighting-1/slimspot-ii-line-lowbay-emergency-light-tws6 192wa



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com