# EASY LINE LOWBAY EMERGENCY LIGHT
# TWTB252WM



| 220-240 V 50/60 Hz AC | 1h | LED | IP 40 | RAL 9003 | 850 °C | -O- | CE | LUMi TEST | EN 1838 | EN 60598-2-22 |

## Self-contained emergency light with 1 h battery and Lumi Test self-testing

Teknoware Easy Line Lowbay is a versatile and cost-effective emergency light. It provides a long and narrow light pattern that illuminates corridors and escape routes efficiently.

Easy Line Lowbay can easily be surface or semi-flush mounted thanks to its practical design. Easy's wide product family offers an ideal choice when you want a single fixture for your entire property's needs.Teknoware Easy Line Lowbay is a versatile and cost-effective emergency light. It provides a long and narrow light pattern that illuminates corridors and escape routes efficiently.

Easy Line Lowbay can easily be surface or semi-flush mounted thanks to its practical design. Easy's wide product family offers an ideal choice when you want a single fixture for your entire property's needs.Teknoware Easy Line Lowbay is a versatile and cost-effective emergency light. It provides a long and narrow light pattern that illuminates corridors and escape routes efficiently.

Easy Line Lowbay can easily be surface or semi-flush mounted thanks to its practical design. Easy's wide product family offers an ideal choice when you want a single fixture for your entire

property's needs.

| | |
|---|---|
| Product Code | TWTB252WM |
| Feature | Lumi Test |
| Mounting (standard) | ceiling, surface, recess |
| Customs Code | 94056080 |
| GTIN Code | 6438045026671 |
| ETIM Product Class | EC001957 |
| Length | 265 mm |
| Width | 137 mm |
| Height | 53 mm |
| Weight | 0.45 kg |
| Backup | 1 h |
| Max Input Power VA | 8 VA |
| Nominal Supply Voltage | 220-240 V, 50/60 Hz AC |
| Protection Class | II |
| IP Class | IP40 |
| Temperature Range Min - Max | 0...+35 °C |
| Glow Wire Test of Plastic Materials | 850 °C |
| Light Source | LED |
| Body Material | plastic |
| Colour | RAL9003 |
| Electrical Installation | 2/3 x 2,5 mm² |
| Luminous Flux | 170 lm |

# Emergency lighting for escape routes (ceiling mounting)

Table of 1 lux for escape routes in the middle line according to the norm EN 1838.
Level of measurement 0,02 m, measurement result with battery operation.

**Teknoware**®

R1 distance from wall (X axis)
R2 installation distance between lights (X axis)
R4 distance from wall (Y axis)

## TWTB252WM

| Mounting height (m) | Below the light lux | R1 (m) | R2 (m) | R4 (m) |
|---|---|---|---|---|
| | | 1 lux | 1 lux | 1 lux |
| 2,5 | 6.5 | 7 | 17 | 1 |
| 3 | 4.5 | 8 | 19 | 1 |
| 4 | 2.5 | 8 | 23 | 1 |

# OPTIONAL ACCESSORIES:

# SHOCK PROTECTING COVERS FOR EMERGENCY LIGHTS

| Product Code | Product Name | Compatible Product Groups |
|---|---|---|
| TW77508B | Shock protecting cover TW77508B | ESC 0,5 Emergency Exit Lights, ESC 4 Emergency Exit Lights, ESC 90 Emergency Exit Lights, Safe 82 Emergency Lights |

# OTHER ACCESSORIES FOR EMERGENCY LIGHTS

| Product Code | Product Name | Compatible Product Groups |
|---|---|---|
| TWTB110 | Easy Combo IP54 gasket TWTB110 | Other Accessories for Emergency Exit Lights |

# OPTIONAL MOUNTING ACCESSORIES FOR

Teknoware®

# EMERGENCY EXIT LIGHTS

| Product Code | Product Name | Compatible Product Groups |
|---|---|---|
| TWTB101 | Easy Combo recess mounting frame TWTB101 | Easy: Combo Emergency / Exit Light, Easy Combo Emergency / Exit Light |
| TWTB103 | Easy Combo flag bracket TWTB103 | Easy: Combo Emergency / Exit Light, Easy Combo Emergency / Exit Light |
| TWTB104 | Easy Combo ceiling bracket TWTB104 | Easy: Combo Emergency / Exit Light, Easy Combo Emergency / Exit Light |
| TWTB105 | Easy Combo suspension bracket TWTB105 | Easy: Combo Emergency / Exit Light, Easy Combo Emergency / Exit Light |

**TEKNOWARE**®

68  49  Ø 20

38

8

27.5

264

139

52  Ø 20  Ø 20  214

72  72  35  Ø 20

**TEKNOWARE**®