SMOOTH: LINE



















Teknoware Smooth is a small and elegant yet extremely durable emergency light optimised for outdoor use. The Smooth is a combination light, which you can use both as an emergency light and as a 300 lumen general light depending on the model. Because of the stylish design, the luminaire blends seamlessly into the architecture of the building. The Smooth always consists of two units: the luminaire and a separated indoor electronic unit. The Smooth includes a 5-metre fire-proof installation cable between the units. The luminaire is designed for surface mounting on a wall. The Smooth has an impact-resistant cast aluminium casing (IK10), and it is dust- and waterproof (IP65 for the visible part of the luminaire). The standard colour of the luminaire is graphite grey (RAL 7024), other colours are available on request (e.g. white RAL 9003).

The Smooth Line is a compact emergency light designed to illuminate escape routes efficiently. The luminaire provides a long and narrow pattern.

for escape routes

installation height: up to 4 metres

centrally supplied

IP class: IP65 (for the visible part of the luminaire), IP20 (for the separate electronic unit) installation: surface mounting on a wall (also requires installation of the separate electronic unit) includes a 5-metre fire-proof installation cable between the units

material: cast aluminium (IK10)

colour: graphite grey (RAL 7024), other RAL-colours on request

ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS



Product Code	Nominal Supply Voltage	Feature
TWTC851WK	220-240 V, 50/60 Hz AC,DC	Intelligent Controller, Tapsa Control

ADDRESSABLE 24 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWTC841WK	24 V, 50/60 Hz AC, DC	Tapsa Control	

