




# SAFE 29 EMERGENCY LIGHTS



Safe 29 is suited for demanding environmental conditions. It has a plastic frame, and combines functional design with a high protection rating.

For emergency lighting applications, an 18 W model is also available. It allows a higher mounting height. The double insulated construction material is of shock-resistant plastic. Safe 29 is available with either a long-life LEDs, or a fluorescent lamp. The luminaires in the Safe 29 product line are suited for interior and exterior applications. Thanks to the improved LED technology, the new ESCAP models are now available, offering longer mounting distance for both open area (TWS2992WAC) and escape routes (TWS2992WAB). With these new ESCAP models, also 4 m mounting height is now possible.

## ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: April 27, 2024 | Source:

[www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/safe-29-emergency-lights](http://www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/safe-29-emergency-lights)



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland  
Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)

Product Code	Nominal Supply Voltage	Feature
TWT2981K	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control
TWT2984K	220-240 V, 50/60 Hz AC, DC	Tapsa Control
TWT2951WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control

NON-ADDRESSABLE 24 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature
TWT2921	24 V, 50/60 Hz AC, DC	